

IN THE CLAIMS:

Please cancel claims 1-25 and add the following new claims 26-31.

26. An organic electroluminescent device comprising:
- an anode formed of a positive charge carrier injecting material;
 - a cathode formed of a negative charge carrier injecting material;
 - a light emissive layer located between the anode and cathode; and
 - a dielectric layer located between the light emissive layer and the anode.

27. A device as claimed in claim 26, wherein the thickness of the dielectric layer is between 10 and 500Å.

28. An organic electroluminescent device comprising:
- an anode formed of a positive charge carrier injecting material;
 - a cathode formed of a negative charge carrier injecting material;
 - a light emissive layer located between the anode and cathode; and
 - a layer of carbon or amorphous silicon located between the light emissive layer and the anode.

29. A device as claimed in claim 28, wherein the thickness of the carbon or amorphous silicon layer is between 10 and 500Å.

30. An organic electroluminescent device comprising:
- an anode formed of a positive charge carrier injecting material;
 - a cathode formed of a negative charge carrier injecting material;
 - a light emissive layer located between the anode and cathode; and
 - located between the light emissive layer and the anode, a layer of conductive oxide selected from the group consisting of tin oxide, zinc oxide, vanadium oxide, molybdenum oxide and nickel oxide.